

Tabla de Rendimiento Serie D - Acoplada a Motor JM ODP

SERIE	SUCC/DESC	DIAM. IMPULSOR	RPM	LPM	80	120	160	240	320	380	570	760	1140	1520	1900	2280	INFORMACIÓN DEL MOTOR					SOLO BOMBA		
				GPM	20	30	40	60	80	100	150	200	300	400	500	600	HP	AK	EJE	NO. DE PARTE		DIAM. IMPULSOR	MODELO	NO. DE PARTE
				CARGA EN METROS																				
DA1A-6	1.25" x 1"	4.125"	3600	-	18	16	12	-	-	-	-	-	-	-	-	-	0.5	4.5	5/8	307102101	307103101	5.062"	FPDA1A-K1	93167413R011
	1.25" x 1"	4.687"		-	24	22	17	-	-	-	-	-	-	-	-	-	0.75			307104101	307105101		FPDA1A-K1	93167413R011
	1.25" x 1"	5.062"		-	29	27	23	-	-	-	-	-	-	-	-	-	1			307106101	307107101		FPDA1A-K1	93167413R011
DA1B-6	1.25" x 1"	3.75"		-	16	14	12	-	-	-	-	-	-	-	-	-	0.5	4.5	5/8	307102101	307103101	5.062"	FPDA1B-K1	93167413R021
	1.25" x 1"	4"		-	20	19	17	13	-	-	-	-	-	-	-	-	0.75			307104101	307105101		FPDA1B-K1	93167413R021
	1.25" x 1"	4.25"		-	23	22	21	16	-	-	-	-	-	-	-	-	1			307106101	307107101		FPDA1B-K1	93167413R021
	1.25" x 1"	4.687"		-	29	28	27	23	-	-	-	-	-	-	-	-	1.5			307108101	307109101		FPDA1B-K1	93167413R021
	1.25" x 1"	5.062"		-	35	34	33	30	-	-	-	-	-	-	-	-	2			307110101	307111101		FPDA1B-K1	93167413R021
DB1-6	1.5" x 1"	4.25"		-	-	17	15	10	-	-	-	-	-	-	-	-	0.75	4.5	5/8	307				