

Output Ratings		
Generating Set Model	P32P5S	P35E5S
220-240V, 50 Hz	32.0 kVA 32.0 kW	35.0 kVA 35.0 kW
480V, 60 Hz	36.0 kVA 36.0 kW	40.0 kVA 40.0 kW

Ratings at 0.8 pf

Ratings Definitions

Prime Power – Model P32P5S

These ratings are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. There is no limitation to the annual hours of operation and this model can supply 10% overload power for 1 hour in 12 hours.

Standby Power – Model P35E5S

These ratings are applicable for supplying continuous electrical power (at variable load) in the event of a utility power failure. No overload is permitted on these ratings. The alternator on this model is peak continuous rated (as defined in ISO 8528-3).

Technical Data		
Engine Model:	Perkins 1104A-44G	
Alternator Model:	LL2014H	
Number of Cylinders:	4 In Line	
Displacement: litres (cu.in)	4.4 (268.5)	
Bore/Stroke: mm (in)	105.0 (4.1)/127.0 (5.0)	
Compression ratio:	19.25:1	
Induction:	Naturally Aspirated	
Frequency:	50 Hz	60 Hz
Engine Speed:	1500 RPM	1800 RPM
Gross Engine Power: kW (hp)	45.0 (60.0)	54.0 (72.0)
BMEP: kPa (psi)	818.0 (118.7)	818.0 (118.7)
Piston Speed: m/sec (ft/sec)	6.4 (20.8)	7.6 (25.0)
Fuel Tank Capacity: litres (US gal)	175 (46.2)	175 (46.2)
Fuel Consump, P32P5S: l/hr (US g/hr)	13.0 (3.4)	16.0 (4.2)
Fuel Consump, P35E5S: l/hr (US g/hr)	14.5 (3.8)	18.9 (5.0)
Heat Rejected to Exhaust System: kW (Btu/min)	38.0 (2161)	48.0 (2730)
Heat Rejected to Water & Lube Oil: kW (Btu/min)	27.4 (1558)	31.0 (1763)
Heat Radiation to Room: kW (Btu/min)	9.0 (512)	8.0 (455)
Exhaust Gas Temperature: °C (°F)	520 (968)	535 (995)
Radiator Cooling Air Flow: m ³ /min (cfm)	74.4 (2627)	97.8 (3454)
Cooling system designed to operate in ambient conditions up to 50°C (122°F)*		
Combustion Air Flow: m ³ /min (cfm)	2.8 (99)	3.4 (120)
Exhaust Gas Flow: m ³ /min (cfm)	6.9 (244)	9.5 (335)

*Contact your local FG Wilson dealer for power ratings at specific site conditions.

Dimensions and Weights				
Length: mm (in)	Width: mm (in)	Height: mm (in)	Dry: kg (lb)	Wet: kg (lb)
2150 (84.6)	752 (29.6)	1366 (53.8)	974 (2147)	987 (2176)
Dry = With Lube Oil		Wet = With Lube Oil and Coolant		

Ratings in accordance with ISO 8528, ISO 3046, IEC 60034, BS5000 and NEMA MG-1/22.
Generating set pictured may include optional accessories.

Generator set picture may contain non-standard options



www.FGWilson.com



P32P5S / P35E5S



FG Wilson has manufacturing facilities in the following locations:

Northern Ireland • Brazil • China • India • USA

With headquarters in Northern Ireland, FG Wilson operates through a Global Dealer Network. To contact your local Sales Office please visit the FG Wilson website at www.FGWilson.com

